

# SAFETY DATA SHEET

**Date Printed:** 05/23/2024 **Date Revised:** 01/15/2022

## **SECTION 1. IDENTIFICATION**

Product Identifier: (3N) 99.9% Lithium Sulfate Solution

Product Code: LI-SAT-03-SOL

**CAS Number:** 10377-48-7

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551

Fax: +1 310-208-0351

Emergency telephone number:

+1 800-424-9300

## **SECTION 2. HAZARDS IDENTIFICATION**

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 GHS Label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

3.2 Mixtures

Formula: Li2O4S

Molecular Weight: 109.94 g/mol

Hazardous components

**Component Classification Concentration** 

Lithium sulphate

CAS-No. EC-No. 10377-48-7 233-820-4

Acute Tox. 4; H302 10 - 30 %

## **SECTION 4. FIRST AID MEASURES**

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed no data available

#### **SECTION 5. FIREFIGHTING MEASURES**

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Sulphur oxides, Lithium oxides

Sulphur oxides, Lithium oxides

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

5.4 Further information

The product itself does not burn.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for

disposal.

6.4 Reference to other sections

## **SECTION 7. HANDLING AND STORAGE**

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of

workday.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as

NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without

touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after

use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test

method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the

supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It

should not be construed as offering an approval for any specific use scenario.

**Body Protection** 

impervious clothing, The type of protective equipment must be selected according to the concentration and

amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose

combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and

components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Do not let product enter drains.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- 9.1 Information on basic physical and chemical properties
- a) Appearance Form: clear, liquid

Colour: colourless

- b) Odor no data available
- c) Odor Threshold no data available
- d) pH 8.0 9.5 at 188 g/l at 25 °C (77 °F)
- e) Melting point/freezing

point

no data available

f) Initial boiling point and

boiling range

no data available

- g) Flash point not applicable
- h) Evaporation rate no data available
- i) Flammability (solid, gas) no data available
- j) Upper/lower

flammability or

explosive limits

no data available

- k) Vapor pressure no data available
- I) Vapor density no data available
- m) Relative density 1.168 g/cm3 at 20 °C (68 °F)
- n) Water solubility no data available
- o) Partition coefficient: noctanol/

water

no data available

p) Auto-ignition

temperature

no data available

q) Decomposition

temperature

no data available

- r) Viscosity no data available
- s) Explosive properties no data available
- t) Oxidizing properties no data available

#### **SECTION 10. STABILITY AND REACTIVITY**

10.1 Reactivity

no data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

no data available

10.4 Conditions to avoid

no data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Other decomposition products - no data available

In the event of fire: see section 5

#### SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

no data available

Inhalation: no data available Dermal: no data available

no data available

Skin corrosion/irritation

no data available

Serious eye damage/eye irritation

no data available

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Lithium and its compounds are possible teratogens by analogy to lithium carbonate which has equivocal human

teratogenic data and positive animal teratogenic data.

no data available

Specific target organ toxicity - single exposure

no data available

Specific target organ toxicity - repeated exposure

no data available

Aspiration hazard

no data available

Additional Information

RTECS: Not available

Lithium and its compounds are possible teratogens by analogy to lithium carbonate which has equivocal human

teratogenic data and positive animal teratogenic data., Ingestion of even small amounts of cyanide compounds can

cause:, Large doses of lithium ion have caused dizziness and prostration, and can cause kidney damage if sodium

intake is limited. Dehydration, weight loss, dermatological effects, and thyroid disturbances have been reported. Central

nervous system effects that include slurred speech, blurred vision, sensory loss, ataxia, and convulsions may occur.

Diarrhea, vomiting, and neuromuscular effects such as tremor, clonus, and hyperactive reflexes may occur as a result

of repeated exposure to lithium ion.

Liver - Irregularities - Based on Human Evidence

Liver - Irregularities - Based on Human Evidence (Lithium sulphate)

## **SECTION 12. ECOLOGICAL INFORMATION**

12.1 Toxicity

Toxicity to daphnia and

other aquatic

invertebrates

EC50 - Daphnia magna (Water flea) - 196.79 mg/l - 24 h

12.2 Persistence and degradability:

no data available

12.3 Bioaccumulative potential:

no data available

12.4 Mobility in soil:

no data available

12.5 Results of PBT and vPvB assessment:

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

no data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

# 13.1 Waste treatment methods

**Product** 

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste

disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a

chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

## **SECTION 14. TRANSPORT INFORMATION**

DOT (US)

Not dangerous goods

**IMDG** 

Not dangerous goods

IATA

Not dangerous goods

# **SECTION 15. REGULATORY INFORMATION**

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the

threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Water

CAS-No.

7732-18-5

**Revision Date** 

Lithium sulphate 10377-48-7

New Jersey Right To Know Components

Water

CAS-No.

7732-18-5

**Revision Date** 

Lithium sulphate 10377-48-7

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other

reproductive harm.

#### 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED ARENCED ELEMENTS. LICENSED ARENCED ELEMENTS. LICENSED

TEL. 310-208-0551 | FAX 310-208-0351 | customerservice@americanelements.com